

# Product Datasheet

## Characteristic

WDE008249

2 Socket-outlet, Exxact, complete product, 2P + E, 16A, Schuko, lid, with shutter, screw, IP44 white



### Main

Range	Exxact
product or component type	Socket-outlet
Device application	Power supply
device presentation	Complete product
Socket number	2
Outlet standard	CEE 7/3
outlet standard	Schuko
[Ue] rated operational voltage	250 V
Network type	AC
Colour tint	White (RAL 9003)

### Complementary

device mounting	Flush
Outlet poles configuration	2P + E
Rated current	16 A
Cover type	Lid With shutter
Fixing mode	By screws
Connections - terminals	Screw
Number of loop terminals	2
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC (polycarbonate) PC
Depth	47.0 mm
Embedding depth	22 mm
Height	82 mm
Width	100 mm
Projecting depth	25 mm

### Environment

IP degree of protection	IP44
Standards	IEC 60884-1
Product certifications	NEMKO SEMKO FIMKO

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.700 cm
Package 1 Width	12.100 cm
Package 1 Length	18.500 cm
Package 1 Weight	138.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	13.000 cm
Package 2 Width	19.600 cm
Package 2 Length	26.600 cm
Package 2 Weight	780.000 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	&nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2306012EN
Circularity Profile	N/A