

Product Datasheet

Characteristic

WDE011303

Renova - single socket outlet - 2P + E - 16 A - 250 V - black



Main

Range	Renova
product or component type	Socket-outlet
device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

Complementary

Socket number	1
device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard	CEE 7/3
outlet standard	Schuko
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	Black (NCS S 9000-N)
Connections - terminals	Screwless terminals
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC/ABS
Fixing mode	By screws and claws
Diameter	71 mm
Embedding depth	28 mm
Projecting depth	15 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004
Product certifications	SEMKO FIMKO
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	7.100 cm
Package 1 Length	7.100 cm
Package 1 Weight	67.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	8.500 cm
Package 2 Width	22.800 cm
Package 2 Length	8.800 cm
Package 2 Weight	376.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	33.000 cm
Package 3 Width	39.400 cm
Package 3 Length	30.000 cm
Package 3 Weight	6.482 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP1507006
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins