

# Product Datasheet

## Characteristic

# WDE011322

## Renova - double socket outlet - 2P + E - 16 A - 250 V - black



### Main

Range	Renova
product or component type	Socket-outlet
device presentation	Mechanism with fixing frame
Quantity per set	Set of 5
Product compatibility	To be completed with Renova frame

### Complementary

Socket number	2
device mounting	Flush
Outlet poles configuration	2P + E
Outlet standard	CEE 7/3
outlet standard	Schuko
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Colour tint	Black (NCS S 9000-N)
Connections - terminals	Screw terminals
Number of loop terminals	2
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid cable(s) 1 x 1.5...2 x 2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC/ABS
Fixing mode	By screws and claws
Width	71 mm
Height	92 mm
Embedding depth	22 mm
Projecting depth	22 mm

### Environment

Standards	DIN VDE 0620-1 IEC 60884-1 SS 4280834 SFS 5610:2004 NEK 502:2006
-----------	--

Product certifications	SEMKO NEMKO FIMKO
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	7.100 cm
Package 1 Length	9.700 cm
Package 1 Weight	65.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	10.300 cm
Package 2 Width	9.500 cm
Package 2 Length	26.300 cm
Package 2 Weight	521.000 g
Unit Type of Package 3	P12
Number of Units in Package 3	1440
Package 3 Height	105.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	178.488 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	Free of Substances of Very High Concern above the threshold
REACH free of SVHC	Yes
EU RoHS Directive	Compliant
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	&nbsp;Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP2303021EN
Circularity Profile	N/A