


# Product Datasheet

## Characteristic

# XAPD31

Die cast empty control station,  
Harmony XAP, XB2 SL, zinc alloy, grey,  
M25, undrilled, 80x175x51,5mm



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Harmony XAP  |
| product or component type     | Die-cast empty control station                       |
| Device short name             | XAPD   |
| product destination           | For Ø 22 mm control and signalling units             |
| Product front plate size      | 80 x 175 mm  |
| Usable depth                  | 49 mm  |
| Number of cut-out             | Without cut-out                                      |
| Colour of base of enclosure   | Grey (RAL 7035)                                      |
| Colour of cover               | Grey (RAL 7035)                                      |
| Material                      | Die cast zinc  |
| Sale per indivisible quantity | 1  |
| IP degree of protection       | IP65 conforming to EN/IEC 60529 and EN/IEC 60947-5-1 |

## Complementary

|                           |                                   |
|---------------------------|-----------------------------------|
| Number of vertical rows   | 0                                 |
| Number of horizontal rows | 0                                 |
| Control station type      | Metal                             |
| Cable entry               | 2 x cable gland conforming to ISO |
| Thread type               | M25 x 1.5                         |
| CAD overall width         | 80 mm                             |
| CAD overall height        | 175 mm                            |
| CAD overall depth         | 51.5 mm                           |
| net weight                | 0.87 kg                           |

## Environment

|                                       |  |
|---------------------------------------|--|
| protective treatment                  | TC   |
| Ambient air temperature for storage   | -40...70 °C                                  |
| Ambient air temperature for operation | -25...70 °C                                  |
| Electrical shock protection class     | Class I conforming to IEC 61140              |
| IK degree of protection               | IK07 conforming to IEC 62262                 |
| Resistance to chemical agents         | Special treatment can be obtained on request |

|                        |     |
|------------------------|-----|
| Product certifications | EAC |
|------------------------|-----|

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 8.8 cm   |
| Package 1 Width              | 12.0 cm  |
| Package 1 Length             | 18.3 cm  |
| Package 1 Weight             | 1.002 kg |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 6        |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 6.408 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                                       |
| REACH Regulation           | Free of Substances of Very High Concern above the threshold |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | X   |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | ENVPEP2111017EN   |
| Circularity Profile        | N/A   |