Product Datasheet

Characteristic

XVBC2B4

Indicator bank, Harmony XVB, illuminated unit, plastic, red, 70mm, steady, integral LED, 24V AC/DC





Main

| Range of product | Harmony XVB Universal | |
|------------------------------------|-----------------------|--|
| product or component type | Indicator bank | |
| Beacon or indicator bank unit type | Illuminated unit | |
| Signalling type | Steady | |
| Mounting diameter | 70 mm | |
| Component name | XVBC | |
| Material | Polycarbonate | |
| Light source | Integral LED, red | |
| Bulb type | Protected LED | |
| [Us] rated supply voltage | 24 V AC/DC | |

Complementary

| · · · · · · · · · · · · · · · · · · · | |
|--|--|
| Assembly style | Customer assembly, up to 5 units |
| Connections - terminals | Screw clamp terminals, <= 1 x 1.5 mm² with cable end |
| [Ui] rated insulation voltage | 250 V conforming to IEC 60947-1 |
| Nominal voltage limit | 0.851.1 Un conforming to IEC 60947-5-1 |
| Current consumption | < 47 mA AC/DC |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60947-1 |
| CAD overall width | 70 mm |
| CAD overall height | 63 mm |
| CAD overall depth | 70 mm |
| net weight | 0.15 kg |
| | |

Environment

| Pollution degree | 2 | |
|-------------------------------------|---|--|
| Product certifications | CCC EAC CSA C22-2 No 14 UL 508 | |
| Standards | EN/IEC 60947-5-1 | |
| protective treatment | TC | |
| Ambient air temperature for storage | -4070 °C | |

| Ambient air temperature for operation | -2550 °C |
|---------------------------------------|--|
| Electrical shock protection class | Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140 |
| IP degree of protection | IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529 |
| NEMA degree of protection | Type 4X conforming to UL (indoor) |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.3 cm |
| Package 1 Width | 10 cm |
| Package 1 Length | 10 cm |
| Package 1 Weight | 135 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 36 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 5.419 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 288 |
| Package 3 Height | 80 cm |
| Package 3 Width | 80 cm |
| Package 3 Length | 60 cm |
| Package 3 Weight | 53.084 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| Mercury free | Yes | |
| China RoHS Regulation | Х | |
| RoHS exemption information | Yes | |
| Environmental Disclosure | ENVPEP070907EN | |
| Circularity Profile | N/A | |
| WEEE | The product must be disposed on European Union markets following | |