Product Datasheet

Characteristic

XVLA133

Pilot light, Harmony XVL, plastic, green, 8mm, protruding LED, faston connectors, 24V DC





Main

Range of product	Harmony XVL	
product or component type	LED pilot light with black bezel	
Component name	XVL	
Mounting diameter	8 mm	
Light source	Protruding LED	
Light block colour	Green	
Protection type	Integral ballast resistor Built-in by diode	
[Us] rated supply voltage	24 V	
IP degree of protection	IP40 conforming to IEC 60529 IP40 conforming to NF C 20-010	

Complementary

Supply circuit type	DC	
Connections - terminals	Tag for Faston connectors: 2.8 x 0.5 mm Tag for soldering connectors	
Current consumption	18 mA	
[Ui] rated insulation voltage	50 V conforming to IEC 60947-1	
Bulb lifespan	100000 h	
Nominal voltage limit	0.81.1 Un	
Terminals description ISO n°1	(X1-X2)PL	
Height	12 mm	
Width	12 mm	
Depth	34 mm	
net weight	0.003 kg	

Environment

Product certifications	CSA UL
protective treatment	TC
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.2 cm
Package 1 Width	1.2 cm
Package 1 Length	4.2 cm
Package 1 Weight	3.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.0 cm
Package 2 Width	10.0 cm
Package 2 Length	11.0 cm
Package 2 Weight	31.0 g
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	15.0 cm
Package 3 Width	15.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	509.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	Х
RoHS exemption information	Yes
Environmental Disclosure	ENVPEP111048EN
Circularity Profile	N/A
WEEE	The product must be disposed on European Union markets following