

Product Datasheet

Characteristic

XVLA334

Pilot light, Harmony XVL, plastic, red,
12mm, covered LED, 24V DC



Main

| | |
|---------------------------|--|
| Range of product | Harmony XVL |
| product or component type | LED pilot light with integral lens cap |
| Component name | XVL |
| Mounting diameter | 12 mm |
| Light source | Covered LED |
| Light block colour | Red |
| Protection type | Built-in by diode Integral ballast resistor |
| [Us] rated supply voltage | 24 V |
| IP degree of protection | IP65 (with seal XVLZ912) conforming to IEC 60529 IP65 (with seal XVLZ912) conforming to NF C 20-010 IP40 conforming to IEC 60529 IP40 conforming to NF C 20-010 |

Complementary

| | |
|-------------------------------|---|
| Supply circuit type | DC |
| Connections - terminals | Threaded connector: clamping capacity 1 x 0.2...1 x 1.5 mm ² |
| Current consumption | 18 mA |
| [Ui] rated insulation voltage | 50 V conforming to IEC 60947-1 |
| Bulb lifespan | 100000 h |
| Nominal voltage limit | 0.8...1.1 Un |
| Terminals description ISO n°1 | (X1-X2)PL |
| Height | 16 mm |
| Width | 16 mm |
| Depth | 51 mm |
| net weight | 0.007 kg |

Environment

| | |
|---------------------------------------|-------------|
| Product certifications | UL CSA |
| protective treatment | TC |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |

| | |
|----------------------|--|
| Overvoltage category | Class 3 conforming to IEC 60536 Class 3 conforming to NF C 20-030 |
|----------------------|--|

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.500 cm |
| Package 1 Width | 2.500 cm |
| Package 1 Length | 4.500 cm |
| Package 1 Weight | 7.600 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 3.000 cm |
| Package 2 Width | 14.000 cm |
| Package 2 Length | 10.000 cm |
| Package 2 Weight | 76.000 g |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 100 |
| Package 3 Height | 15.000 cm |
| Package 3 Width | 15.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 970.000 g |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | X |
| RoHS exemption information | Yes |
| Environmental Disclosure | ENVPEP111048EN |
| Circularity Profile | N/A |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |