Product Datasheet

Characteristic

ZB5AD28

Toggle switch head, Harmony XB5, plastic, black, 22mm, 2 positions, stay put



Main

Range of product	Harmony XB5
product or component type	Head for selector switch
Device short name	ZB5
Bezel material	Dark grey plastic
Mounting diameter	22 mm
Sale per indivisible quantity	1
Head type	Standard
Shape of signaling unit head	Round
Type of operator	stay put
Operator profile	Black toggle switch
Operator additional information	Black lever
Operator position information	2 positions 90°

Complementary

CAD overall width	29 mm
CAD overall height	29 mm
CAD overall depth	45 mm
net weight	0.023 kg
Mechanical durability	500000 cycles
Station name	XALD 15 cut-outs XALK 25 cut-outs
Electrical composition code	C11 for <3 contacts using single blocks in front mounting C12 for <6 contacts using single blocks in front mounting C15 for <1 contacts using single blocks in front mounting SF1 for <3 contacts using single blocks in front mounting SR1 for <3 contacts using single blocks in rear mounting C13 for <6 contacts using single and double blocks in front mounting
device presentation	Basic element

Environment

2. Transferred	
protective treatment	TH
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C
Overvoltage category	Class II conforming to IEC 60536
IP degree of protection	IP66 conforming to IEC 60529

NEMA degree of protection	NEMA 13
	NEMA 4X
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m
IK degree of protection	IK06
Standards	IEC 60947-5-1
	IEC 60947-5-4
	CSA C22.2 No 14
	UL 508
	IEC 60947-1
	JIS C8201-5-1
	JIS C8201-1
Product certifications	DNV
	GL
	UL listed
	BV
	CSA
	LROS (Lloyds register of shipping)
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27
	50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Packing Units

racking onits		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.500 cm	
Package 1 Width	4.500 cm	
Package 1 Length	5.500 cm	
Package 1 Weight	22.000 g	
Unit Type of Package 2	S03	
Number of Units in Package 2	200	
Package 2 Height	30.000 cm	
Package 2 Width	30.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	4.774 kg	
Unit Type of Package 3	P06	
Number of Units in Package 3	1600	
Package 3 Height	75.000 cm	
Package 3 Width	80.000 cm	
Package 3 Length	60.000 cm	
Package 3 Weight	46.192 kg	

Offer Sustainability

REACh Regulation	Free of Substances of Very High Concern above the threshold
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	Х
RoHS exemption information	Yes