



FPKu-ES-F-UV black

43411



Product description:

FPKu-ES-F-UV black is a heavy duty straight length conduit made of modified PVC, in black (RAL 9005), non-flame propagating, UV-stabilised, in lengths of 3 m, with one pre-moulded coupling.

This straight length plastic conduit is used for exposed installation outdoor and for installation in industrial facilities. Advantages are its heavy compressive strength and corrosion resistance against acids and bases.



VDE 0605
DIN EN 61386-21
minimum compressive strength: 1250 N/5 cm



Special features

UV-resistant for up to 10 years.

Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg
226 10 020	20	16,6	20,0	57	m	7,695
226 10 025	25	21,2	25,0	57	m	10,374
226 10 032	32	27,9	32,0	21	m	5,460
226 10 040	40	35,3	40,0	21	m	7,350
226 10 050	50	45,4	50,0	21	m	10,185

Classification	Code	Meaning	Classification	Code	Meaning
Compressive strength	4	heavy (1250 N)	Protection against solids	4	Foreign matter >= 1.0 mm
Impact strength	3	medium (2.0 kg/100 mm)	Protection against water	0	Not specified
Minimum temperature	4	- 25 °C	Corrosion protection	0	Not specified
Maximum temperature	1	+ 60 °C	Tensile strength	0	Not defined
Bending behaviour	1	rigid	Fire behaviour	1	Non flame propagating
Electrical characteristics	2	Insulation	Suspended load	0	Not defined

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 60423 / IEC 60423

All dimensions without tolerances are for information only.

FRÄNKISCHE ROHRWERKE Gebr. Kirchner GmbH & Co. KG | Hellinger Str. 1 | 97486 Königsberg/Bayern
Hotline +49 9525 88-8123 | Fax +49 9525 88-2151 | info.elektro@fraenkische.com | www.fraenkische.com

Subject to change without notice.

Page 1 of 2

Last modified: 30.05.17



FPKu-ES-F-UV black

43411

Material properties		Fields of application	
Zero halogen	DIN VDE V 0604-2-100	on plaster	• machines
Low smoke	DIN EN 61034-2	under plaster	• hot asphalt
Non-flame propagating	DIN EN 61386-1	• on wood	• under screed
UV-resistant	DIN 53387	• underground installation	• prefabricated construction
Highspeed		in concrete	• outdoor

Chemical properties	
Resistant to	hydrochloric acid emissions, sulphuric acid emissions, liquid ammonia, gaseous ammonia, gasoline, diesel fuel, aqueous fertiliser salt, photographic developer, vinegar (wine vinegar), anti-freeze, fruit juices, aqueous uric acid, fuel oil, sea water, methanol, milk, mineral oil, vegetable and animal oils, paraffin, gaseous propane, nitric acid, hydrochloric acid, sulfuric acid, turpentine, detergent
Limitedly resistant to	gaseous dry chlorine
Not resistant to	benzene, beer

Accessories		
Push-fit coupling	SMSKu-E-UV black	225 51 ...
Push-fit elbow	SBSKu-ES-UV black	226 61 ...
Clamp	clipfix-UV black	225 71 ...
End cap	E-Ku-E black	259 96 ...
Divisible end cap	E-Ku-ET-UV	259 98 ...

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

