

NPR-1700-RT
NETYS PR RT 1700VA RK/TW

Strong points

- A secure and professional supply continuity
- Tailored to IT networking
- Simple to install
- Protection for your data line
- Meets practical needs
- Easy to use and to integrate

General characteristics

- 19" Rack & Rack/Tower convertible UPS.
- Sine Wave, AVR function (Automatic Voltage Regulation).
- Clear and uncluttered LCD interface.
- Wide range of communication protocols available in options.
- NTP data line suppressor.
- Up to 9 UPS output sockets.

Compliance with standards

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

Link to the reference

The NETYS PR is the ideal solution for protecting small servers, networking devices and peripherals.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	NeTYS PR-RT 1700VA/1350W 230V 50/60Hz WITH AVR, SINEWAVE, LCD PLUGS PROTECTED RJ45, 1xUSB, 1xRS232 BATTERY INCLUDED
Effective date	2012-09-01
Country of origin	CN
Length of the product unit	0.087
Width of the product unit	0.44
Depth of the product unit	0.436
Weight	18

ETIM - Electrical characteristics

Input voltage [V]	161..276
Primary frequency [Hz]	45..66
Number of phases primary	1
Output voltage [V]	230..230
Secondary frequency [Hz]	50..60
Output effective power [W]	1350
Output apparent power [VA]	1700
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Output power factor	0.8

ETIM - Mechanical characteristics

Height [mm]	87
Width [mm]	440
Depth [mm]	436
Weight [kg]	18
Construction type	Free standing model
Input connection	C14
Number of output connections C13	8

ETIM - Technical features

USB interface	No
Bridging time full load [min]	8.4
Suitable for network-management	Yes
USV- technology	Line-interactive
Overall efficiency [%]	98
Efficiency in eco-mode [%]	98
Potential free switch contact	Yes
Auto shut down function	Yes

Logistics

GTIN/EAN	8027122515320
----------	---------------

Customs number	8504409590
Weight of the packing unit	18
Length of the packing unit	0.436
Width of the packing unit	0.44
Depth of the packing unit	0.087
Norms	
Conformity to standards	IEC
Technical Characteristics	
Depth	436
Height	87
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn	1.7
Pn	1.35
Conf	M2
Input voltage	230
Rate (min)	1.7
Rate (max)	1.7
Life Time	03-05
Typical Backup Time	7
Configuration	Line-Interactive UPS with AVR