

Eaton 182960

Catalog Number: 182960

Eaton Moeller® series M30 Pushbutton, RMQ-Titan, Flat, momentary, White, Blank, Metal bezel



General specifications

Product Name	Catalog Number
Eaton Moeller® series M30 Pushbutton	182960
EAN	Product Length/Depth
4015081778874	36 mm
Product Height	Product Width
30 mm	46 mm
Product Weight	Warranty
0.041 kg	
	Certifications
	IEC/EN 60947
	VDE 0660
	CSA File No.: 012528
	CSA Class No.: 3211-03
	DNV
	UL File No.: E29184
	GL
	IEC/EN 60947-5
	UL 508
	CSA-C22.2 No. 14-05 and 94-M91
	CE marking
	UL Category Control No.: NKCR
	UL Listed
	CSA certified

Omadused ja funktsioonid

Bezel color

Titanium

Bezel material

Metal

Design

Flat

Flat front

Fitted with:

Front ring

Inscription

Blank

Üldist

Degree of protection

IP66

IP67

IP69K

Degree of protection (front side)

IP67/IP69K

NEMA 4X, 13

Lifespan, mechanical

5,000,000 Operations

Opening diameter

30.5 mm

Operating frequency

3600 Operations/h

Product category

RMQ-Titan

Product category

RMQ-Titan

Size

Front dimensions: Ø 36 x 3 mm

Type

Pushbutton actuator

Used with

M22 contact blocks and indicating lights

Keskkonningimused, mehaanilised

Mounting position

As required

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Ilmastikutingimused

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Aktuaator

Actuating force

5 N

Actuator color

White

Actuator function

Spring-return

Momentary

Kommunikatsioon

Connection to SmartWire-DT

Yes

With SWD-RMQ connections

Kontaktid

Force for positive opening - min

0 N

Lisainfo

eCAD model

ETN.182960.edz

Joonised

[eaton-operating-m30-dimensions-005.eps](#)

[eaton-operating-m30-dimensions.eps](#)

[eaton-operating-m30-dimensions-004.eps](#)

[eaton-operating-m30-dimensions-006.eps](#)

[eaton-operating-button-symbol-013.eps](#)

[eaton-operating-m30-3d-drawing.eps](#)

mCAD model

[DA-CS-drucktaste_flach_flatfront](#)

[DA-CD-drucktaste_flach_flatfront](#)

Multimedia

[RMQ small E-Stop emergency-stop button](#)

Paigaldusjuhised

[eaton-operating-devices-m30-rmq-titan-flat-front-instruction-leaflet-il047019zu.pdf](#)

System overview

[Pilot devices - selection aid](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Kõik õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)