

# Eaton 216376

Catalog Number: 216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10



### General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Accessory	216376
Contact element	EAN
	4015082163761
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
32 mm	0.01 kg
Compliances	Certifications
CE Marked	CSA Std. C22.2 No. 94-91
	UL 508
	IEC 60947-5
	CSA Std. C22.2 No. 14-05
	EN 60947-5
	VDE
	CSA File No.: 012528
	CSA-C22.2 No. 14-05
	CSA-C22.2 No. 94-91
	CSA
	UL Category Control No.: NKCR
	UL File No.: E29184
	UL/CSA
	CE
	IEC/EN 60947-5
	IEC
	IEC 60947-5-1
	CSA Class No.: 3211-03
	UL

## Omadused ja funktsioonid

### Electric connection type

Screw connection

## Üldist

### Degree of protection

IP20

### Lifespan, electrical

1,000,000 Operations (at 230 V, AC-15, 1 A)

700,000 Operations (at 230 V, AC-15, 3 A)

1,200,000 Operations (at 12 V, DC-13, 2.8 A)

1,600,000 Operations (at 230 V, 0.5 A)

### Lifespan, mechanical

5,000,000 Operations

### Model

Top mounting and integrable

### Mounting method

Front fastening

### Operating frequency

3600 Operations/h

### Operating torque

0.8 Nm

### Overvoltage category

III

### Pollution degree

3

### Product category

Accessories

### Product category

Accessories

### Rated impulse withstand voltage (Uimp)

6000 V AC

### Type

Auxiliary contact

### Used with

Can be used with NZM2 size circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM3, 4 circuit-breaker: up to three standard auxiliary contacts can be clipped into the circuit-breaker.

Can be used with NZM1 circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM4 circuit-breaker: up to two standard auxiliary contacts can be clipped into the circuit-breaker.

Can be used with NZM1, 2, 3 circuit-breaker: a trip-indicating auxiliary contact can be clipped into the circuit-breaker.

## Ilmastikutingimused

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Ambient storage temperature - max

85 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

## Keskkonnatingimused, mehaanilised

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

## Klemmide ristlõige

Terminal capacity (flexible with ferrule)

0.5 - 1.5 mm<sup>2</sup>

Terminal capacity (solid)

0.75 - 2.5 mm<sup>2</sup>

Terminal capacity (solid/flexible with ferrule)

1 x (0,75 - 2,5) mm<sup>2</sup>

2 x (0,75 - 2,5) mm<sup>2</sup>

Terminal capacity (stranded)

0.5 - 2.5 mm<sup>2</sup>

## Elektrilised andmed

Conventional thermal current *I*<sub>th</sub> of auxiliary contacts (1-pole, open)

4 A

Rated insulation voltage (*U*<sub>i</sub>)

500 V

Rated operational current (*I*<sub>e</sub>)

1 A - 250 V DC

5 A – 600 V AC

Rated operational current (*I*<sub>e</sub>) at AC-15, 115 V

6 A

Rated operational current (*I*<sub>e</sub>) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (*I*<sub>e</sub>) at AC-15, 380 V, 400 V, 415 V

4 A

Rated operational current (*I*<sub>e</sub>) at AC-15, 500 V

2 A

Rated operational current (*I*<sub>e</sub>) at DC-13, 110 V

0.6 A

Rated operational current (*I*<sub>e</sub>) at DC-13, 220 V, 230 V

0.3 A

Rated operational current (I<sub>e</sub>) at DC-13, 24 V

3 A

Rated operational current (I<sub>e</sub>) at DC-13, 42 V

1.7 A

Rated operational current (I<sub>e</sub>) at DC-13, 60 V

1.2 A

Rated operational voltage (U<sub>e</sub>) at AC - max

500 V

Rated operational voltage (U<sub>e</sub>) at DC - max

220 V

## Lühistaluvus

### Short-circuit protection

PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless

### Short-circuit protection rating

Max. 10 A gG/gL, Fuse, Auxiliary contacts

Max. 10 A gG/gL, Fuse, Contacts

## Kommunikatsioon

### Connection to SmartWire-DT

No

### Connection type

Front fixing

Single contact

## Aktuaator

Actuating force - max

5 N

## Kontaktid

### Control circuit reliability

1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)

1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

### Force for positive opening - min

0 N

### Number of contacts (change-over contacts)

0

### Number of contacts (normally closed contacts)

0

### Number of contacts (normally open contacts)

1

## Vastavusavaldus

Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

Heat dissipation capacity P<sub>diss</sub>

0 W

## Lisainfo

eCAD model

ETN.216376.edz

Elektriskeemid

eaton-circuit-breaker-contact-m22-contact-element-wiring-diagram-007.eps

Heat dissipation per pole, current-dependent P<sub>vid</sub>

0.11 W

Rated operational current for specified heat dissipation (I<sub>n</sub>)

6 A

Static heat dissipation, non-current-dependent P<sub>vs</sub>

0 W

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

##### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

##### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

##### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

[eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps](#)

[eaton-circuit-breaker-contact-m22-contact-element-wiring-diagram-006.eps](#)

#### Joonised

[eaton-operating-actuation-m22-led-element-dimensions.eps](#)

[eaton-general-standards-000Z425.jpg](#)

[eaton-operating-contact-m22-contact-element-3d-drawing-004.eps](#)

[eaton-operating-adapter-m22-contact-element-flow-diagram.eps](#)

[eaton-operating-devices-adapter-flow-diagram-002.eps](#)

#### mCAD model

[DA-CS-kontaktelement\\_schraube\\_front](#)

[DA-CD-kontaktelement\\_schraube\\_front](#)

#### Multimedia

[RMQ small E-Stop emergency-stop button](#)

#### Paigaldusjuhised

[eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf](#)

[IL04716002Z](#)

#### System overview

[Pilot devices - selection aid](#)

#### Vastavusavaldused

[DA-DC-00004971.pdf](#)

[DA-DC-00004975.pdf](#)

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. Kõik  
õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)