

Eaton 216378

Catalog Number: 216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01



General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Accessory	216378
Contact element	EAN
	4015082163785
Product Length/Depth	Product Height
38 mm	10 mm
Product Width	Product Weight
32 mm	0.01 kg
Compliances	Certifications
CE Marked	CSA Std. C22.2 No. 14-05
	IEC 60947-5
	CSA Std. C22.2 No. 94-91
	UL 508
	EN 60947-5
	VDE
	CSA-C22.2 No. 94-91
	IEC
	IEC 60947-5-1
	CSA
	CSA Class No.: 3211-03
	CSA-C22.2 No. 14-05
	CSA File No.: 012528
	UL
	UL Category Control No.: NKCR
	UL File No.: E29184
	CE
	IEC/EN 60947-5
	UL/CSA

Omadused ja funktsioonid

Electric connection type

Screw connection

Üldist

Degree of protection

IP20

Lifespan, electrical

1,200,000 Operations (at 12 V, DC-13, 2.8 A)

1,600,000 Operations (at 230 V, 0.5 A)

700,000 Operations (at 230 V, AC-15, 3 A)

1,000,000 Operations (at 230 V, AC-15, 1 A)

Lifespan, mechanical

5,000,000 Operations

Model

Top mounting and integrable

Mounting method

Front fastening

Operating frequency

3600 Operations/h

Operating torque

0.8 Nm

Overvoltage category

III

Pollution degree

3

Product category

Accessories

Product category

Accessories

Rated impulse withstand voltage (Uimp)

6000 V AC

Type

Auxiliary contact

Used with

Can be used with NZM3, 4 circuit-breaker: up to three standard auxiliary contacts can be clipped into the circuit-breaker.

Can be used with NZM4 circuit-breaker: up to two standard auxiliary contacts can be clipped into the circuit-breaker.

Can be used with NZM1, 2, 3 circuit-breaker: a trip-indicating auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM2 size circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Can be used with NZM1 circuit-breaker: a standard auxiliary contact can be clipped into the circuit-breaker.

Keskkonnatingimused, mehaanilised

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Ilmastikutingimused

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

-25 °C

Ambient storage temperature - max

85 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Klemmide ristlõige

Terminal capacity (flexible with ferrule)

0.5 - 1.5 mm²

Terminal capacity (solid)

0.75 - 2.5 mm²

Terminal capacity (solid/flexible with ferrule)

2 x (0,5 - 0,75) mm²

1 x (0,75 - 2,5) mm²

Terminal capacity (stranded)

0.5 - 2.5 mm²

Elektrilised andmed

Conventional thermal current Ith of auxiliary contacts (1-pole, open)

4 A

Rated insulation voltage (Ui)

500 V

Rated operational current (Ie)

5 A – 600 V AC

1 A - 250 V DC

Rated operational current (Ie) at AC-15, 115 V

6 A

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V

4 A

Rated operational current (Ie) at AC-15, 500 V

2 A

Rated operational current (Ie) at DC-13, 110 V

0.6 A

Rated operational current (Ie) at DC-13, 220 V, 230 V

0.3 A

Rated operational current (I_e) at DC-13, 24 V

3 A

Rated operational current (I_e) at DC-13, 42 V

1.7 A

Rated operational current (I_e) at DC-13, 60 V

1.2 A

Rated operational voltage (U_e) at AC - max

500 V

Rated operational voltage (U_e) at DC - max

220 V

Lühistaluvus

Rated conditional short-circuit current (I_q)

1 kA

Short-circuit protection

PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless

Short-circuit protection rating

Max. 10 A gG/gL, Fuse, Contacts

Max. 10 A gG/gL, Fuse, Auxiliary contacts

Kommunikatsioon

Connection to SmartWire-DT

No

Connection type

Front fixing

Single contact

Aktuaator

Actuating force - max

5 N

Actuator travel and actuation force (DIN EN 60947-5-1)

4.8 mm

Knob travel

5.7 mm

Kontaktid

Control circuit reliability

1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)

Force for positive opening - min

15 N

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

0

Vastavusavaldus

Equipment heat dissipation, current-dependent P_{vid}

0 W

Lisainfo

eCAD model

ETN.216378.edz

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.11 W

Rated operational current for specified heat dissipation (I_n)

6 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

Elektriskeemid

[eaton-circuit-breaker-contact-m22-contact-element-wiring-diagram-008.eps](#)

[eaton-circuit-breaker-contact-m22-contact-element-wiring-diagram.eps](#)

[eaton-operating-contact-m22-contact-element-wiring-diagram-003.eps](#)

Joonised

[eaton-operating-actuation-m22-led-element-dimensions.eps](#)

[eaton-general-standards-000Z425.jpg](#)

[eaton-operating-contact-m22-contact-element-3d-drawing-004.eps](#)

[eaton-operating-devices-adapter-flow-diagram-003.eps](#)

[eaton-operating-adapter-m22-contact-element-flow-diagram-002.eps](#)

mCAD model

[DA-CD-kontaktelement_schraube_front](#)

[DA-CS-kontaktelement_schraube_front](#)

Multimedia

[RMQ small E-Stop emergency-stop button](#)

Paigaldusjuhised

[eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf](#)

[IL04716002Z](#)

System overview

[Pilot devices - selection aid](#)

Vastavusavaldused

[DA-DC-00004975.pdf](#)

[DA-DC-00004971.pdf](#)

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Kõik
õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia