

Eaton 216388

Catalog Number: 216388

Eaton Moeller® series M22 Blanking plug, gray

General specifications



Product Name	Catalog Number
Eaton Moeller® series M22 Accessory Blanking plug	216388
	EAN
	4015082163884
Product Length/Depth	Product Height
30 mm	30 mm
Product Width	Product Weight
30 mm	0.006 kg
Certifications	Model Code
CE	M22-B

Omadused ja funktsioonid

Color

Gray

Functions

For closing off of spare mounting locations

Material

Plastic

RAL-number

7035

Üldist

Degree of protection

NEMA 12

NEMA 3R

IP69K

IP66

NEMA 13

IP67

NEMA 4X

Degree of protection (front side)

NEMA Other

IP67/IP69K

Opening diameter

22 mm

Ilmastikutingimused

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Kommunikatsioon

Connection to SmartWire-DT

No

Kontaktid

Force for positive opening - min

0 N

Vastavusavaldus

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

Lisainfo

eCAD model

[ETN.216388.edz](#)

Joonised

[eaton-operating-plug-connector-m22-blanking-plug-dimensions.eps](#)

[eaton-operating-button-symbol-007.eps](#)

mCAD model

[DA-CD-blindverschluss](#)

[DA-CS-blindverschluss](#)

Multimedia

[RMQ small E-Stop emergency-stop button](#)

Paigaldusjuhised

[IL04716002Z](#)

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

System overview

Pilot devices - selection aid

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Kõik õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)