Eaton 216441

Catalog Number: 216441

Eaton Moeller® series M22 Button lens, flat white, blank

General specifications

Product Name Catalog Number

Eaton Moeller® series M22 Accessory 216441

Button lens

EAN

4015082164416

Product Length/Depth Product Height

24 mm 3 mm

Product Width Product Weight

24 mm 0.002 kg

Certifications Model Code
CE M22-XDL-W





Omadused ja funktsioonid

Design

Flat

Inscription

Individual inscription possible: \leq 5 characters: letter

height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm

Lens color

White

Üldist

Type

Flat

Used with

M22(S)-DR-X

M22-DG-X

M22(S)-D-X

Ilmastikutingimused

Ambient operating temperature - max

70 °C

Vastavusavaldus

Equipment heat dissipation, current-dependent Pvid

۸ ۱۸

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Lisainfo

eCAD model

ETN.216441.edz

Joonised

eaton-operating-button-symbol-007.eps

mCAD model

DA-CD-tastenplattenlinse_flach

 $DA\text{-}CS\text{-}tastenplatten linse_flach$

Multimedia

RMQ small E-Stop emergency-stop button

Paigaldusjuhised

IL04716002Z

System overview

Pilot devices - selection aid

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. Kõik õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

