

Eaton 216812

Catalog Number: 216812

Eaton Moeller® series M22 Illuminated selector switch actuator, RMQ-Titan, With thumb-grip, momentary, 2 positions, White, Bezel: titanium



General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Illuminated selector switch actuator	216812
	EAN
	4015082168124
Product Length/Depth	Product Height
46 mm	30 mm
Product Width	Product Weight
30 mm	0.013 kg
Compliances	Certifications
CE Marked	IEC 60947-5
	CSA Std. C22.2 No. 94-91
	EN 60947-5
	CSA Std. C22.2 No. 14-05
	UL 508
	VDE
	CSA Class No.: 3211-03
	CSA-C22.2 No. 94-91
	IEC/EN 60947
	CSA File No.: 012528
	UL File No.: E29184
	UL
	UL Category Control No.: NKCR
	CE
	CSA
	CSA-C22.2 No. 14-05
	VDE 0660
	IEC/EN 60947-5

Omadused ja funktsioonid

Bezel color

Titanium

Bezel material

Plastic

Color

White

Design

With thumb-grip

Fitted with:

Front ring

Functions

Stay-put/spring-return function, can be changed with coding parts M22-XC-Y

Üldist

Accessories

Thumb grip

Degree of protection

NEMA 4X, 13

Degree of protection (front side)

IP66

Lifespan, mechanical

100,000 Operations

Opening diameter

22.5 mm

Operating frequency

2000 Operations/h

Operating torque

0.3 Nm

Overvoltage category

III

Pollution degree

3

Product category

RMQ-Titan

Product category

RMQ-Titan

Size

Front diameter: 29.7 mm

Suitable for

Illumination

Switching angle

40 °

Type

Illuminated selector switch actuator

Keskkonnatingimused, mehaanilised

Mounting position

As required

Ilmastikutingimused

Ambient operating temperature - min

-25 °C

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Ambient operating temperature - max

70 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Kommunikatsioon

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Aktuaator

Actuator color

Black

Actuator function

Momentary

Spring-return

Actuator type

Toggle

Number of switch positions

2

Kontaktid

Force for positive opening - min

0 N

Vastavusavaldus

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the

Lisainfo

eCAD model

ETN.216812.edz

Joonised

eaton-operating-button-symbol-013.eps

mCAD model

DA-CS-wahltaste_knebel

DA-CD-wahltaste_knebel

Multimedia

RMQ small E-Stop emergency-stop button

Paigaldusjuhised

IL04716002Z

System overview

Pilot devices - selection aid

switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Kõik õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)