

Eaton 218305

Catalog Number: 218305

Eaton Moeller® series M22 Button lens, flat white, arrow symbol
M22-XDL-W-X7

General specifications

Product Name	Catalog Number
Eaton Moeller® series M22 Accessory Button lens	218305
	EAN
	4015082183059
Product Length/Depth	Product Height
24 mm	3 mm
Product Width	Product Weight
24 mm	0.002 kg
Certifications	Model Code
UL/CSA certification not required	M22-XDL-W-X7

Omadused ja funktsioonid

Design

Flat

Inscription

Individual inscription possible: ≤ 5 characters: letter height 5 mm

Individual inscription possible: > 5 characters: letter height 3 mm

Lens color

White

Ilmastikutingimused

Ambient operating temperature - max

70 °C

Vastavusavaldus

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Rated operational current for specified heat dissipation (I_n)

0 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Lisainfo

eCAD model

ETN.218305.edz

Joonised

116C111

mCAD model

DA-CD-tastenplattenlinse_flach

DA-CS-tastenplattenlinse_flach

Multimedia

RMQ small E-Stop emergency-stop button

Paigaldusjuhised

IL04716002Z

System overview

Pilot devices - selection aid