

Eaton 260166

Catalog Number: 260166

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable, size 1

General specifications



Product Name

Eaton Moeller series NZM operating element

Catalog Number

260166

EAN

4015082601669

Product Length/Depth

75 mm

Product Height

190 mm

Product Width

90 mm

Product Weight

0.595 kg

Compliances

IEC
UL/CSA
RoHS conform

Certifications

UL489
CE marking
UL (Category Control Number DIHS)
IEC60947
CSA certified
CSA (File No. 22086)
CSA-C22.2 No. 5-09
UL (File No. E140305)
CSA (Class No. 1437-01)
UL listed

Model Code

NZM1-XTVD

Type

Accessory
Door coupling rotary handle

Special features

Door coupling rotary handle
for operating the switch
through a closed control
panel door
External warning
plate/designation label can
be clipped on.
Complete including rotary
drive and coupling parts
Extension shaft additionally
required.

Features

Standard: black / gray
Lockable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

Joonised

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-010.eps](#)
[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-009.eps](#)
[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-005.eps](#)
[eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps](#)

mCAD model

[DA-CS-nzm1_xtvd](#)
[DA-CD-nzm1_xtvd](#)

Paigaldusjuhised

[eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf](#)

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock

Frame

NZM1

Used with

NZM1(-4), PN1(-4), N(S)1(-4)

Suitable for

Switch disconnecter

Power circuit breaker

Cover/door type

Door interlock can be modified such that it can be defeated from the outside using a screwdriver

Door interlock not defeated in the locked OFF and ON positions

Door can be opened in OFF

Door interlock can be modified in the unlocked ON position

Lock number

Single lockable

Locking facility

Lockable on the 0 position on the handle using up to 3 padlocks

With door interlock

Degree of protection / NEMA enclosure type

IP66

4X. 12



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Kõik õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia