

Eaton C14G32

Catalog Number: C14G32

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 32 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C14G32
	Packing Unit
	Pack
EAN	Quantity
5027590058988	10
Gross Weight	Length
0.203 kg	74 mm
Width	Height
105 mm	15 mm
Volume	ERP Name
116.55 cm³	SAP-UNITY
Product Length/Depth	Product Height
51 mm	14.3 mm
Product Width	Product Weight
14.3 mm	20.3 g
Compliances	Certifications
CE Marked	IEC 60269
GoST-R	
RoHS Compliant	

Type

fuse

Application

for industrial applications

for general purpose use

Amperage Rating

32 A

Fuse size

14 x 51 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class C gL/gG

Fuse type

C14G

Utilization category

gG (cable protection/equipment protection)

Fuse indicator

Other

Watt losses

3.5 W

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Fuse shape

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Release characteristic

Other

Quantity

10

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Kõik
õigused on kaitstud.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia