

- TRS - RUTASEAL®

Product features TRS - RUTASEAL®

RUTASEAL® - Animation

Product data TRS - RUTASEAL® Metric


Product data TRS - RUTASEAL® PG

Product data TRS - RUTASEAL LIGHT®

Installation TRS - RUTASEAL®

Why a rubber grommet instead of a cable gland?

TRS - RUTASEAL® EPDM Metric RAL7035



Material
Protection class
Temperature range
Test standard

Semko report

Tariff No.
UNSPSC Code
Halogen-Free

EPDM
IP67 acc. to EN 60529
-40°C....+110°C (1)
EN IEC 60670-1:2021+A11 &
EN 60670-1:2005+A1:2013
SE-S-2300448, SE-S-2002163
(M63), SE-S-2100897 (M12F,
M16F)
4016930090
39121431

(1) Unstressed material.

 [Measurements & Variants](#)  [Information](#)  [Downloads](#)



Lightgrey RAL 7035

	Article no.	Size	For cable Ø mm	A mm	B mm	D mm	H mm	H1 mm
T_1458303	M12	4 - 7	12.5	0,5-2	20	12.7	5.4	50
T_1458303-F	M12	4 - 7	12.5	2 - 5	20	12.7	5.4	50
T_1458304	M16	5 - 9	16.5	1-4	21	18	10.5	50
T_1458304-F	M16	5 - 9	16.5	2 - 5	21	18	10.5	50
T_1458305	M20	8 - 13	20.5	1-4	25.5	20	12.7	50
T_1458306	M25	11 - 17	25.5	1-4	30.5	21.6	14.5	50
T_1458307	M32	15 - 20	32.5	1-4	38.5	24.8	17.5	25
T_1458308	M40	19 - 28	40.5	1-4	48.5	30	20.4	25
T_1458309	M50	27 - 35	50.5	1-4	60.5	35	23.9	10
T_1458337	M63	34 - 45	63.5	1-4	73.5	40	28.9	5

Tapper Sealing Technology AB
Lerbacksgatan 2
SE-571 38 Nässjö
Sweden

Tel: [to contact page](#)
Email: [info \(at\) tst-ab.com](mailto:info@tst-ab.com)

Designed and

Made in Sweden