

- TRS - RUTASEAL®

Product features TRS - RUTASEAL®

RUTASEAL® - Animation


Product data TRS - RUTASEAL® Metric

Product data TRS - RUTASEAL® PG

Product data TRS - RUTASEAL LIGHT®

Installation TRS - RUTASEAL®

Why a rubber grommet instead of a cable gland?



Material

Protection class

Temperature range

Test standard

Semko report

Tariff No.

UNSPSC Code

Halogen-Free

EPDM

IP67 acc. to EN 60529

-40°C....+110°C (1)

EN IEC 60670-1:2021 + A11

2400058

4016930090

39121431

(1) Unstressed material.

 Measurements & Variants  Information  Downloads



Lightgrey RAL 7035

			Article no.	Size	For cable Ø mm	A mm	B mm	D mm
T_1458334	M16	5 - 9	16.5	1-4	21	18	10.5	50
T_1458335	M20	8 - 12	20.5	1-4	25.5	20	12.7	50
T_1458336	M25	11 - 16	25.5	1-4	30.5	21.6	14.5	50

Tapper Sealing Technology AB
Lerbacksgatan 2
SE-571 38 Nässjö
Sweden

Tel: [to contact page](#)
Email: [info \(at\) tst-ab.com](mailto:info@tst-ab.com)

Designed and

Made in Sweden