

## ERM70-E4A – Current Transformer

Flexible, compact and reliable, those are the keywords of the ERM-series of ELEQ. All transformers are equipped with a sealable integrated terminal cover in a case of polycarbonate. The current transformers are supplied with mounting hardware for mounting on rail, cable or mounting plate. Optional the transformers can be ordered with clips which can be used to place the transformers on top hat rail. The ERM-series is KEMA certified.



### Ordering Specifications


Ratio	Class 0.5 VA	Class 1 VA	Class 3 VA	Article Number
600/5A		5	7,5	4M3403E
750/5A	5	7,5	10	4M3401E
800/5A	5	7,5	10	4M3402E
600/1A		5	7,5	4M3412E
750/1A	5	7,5	10	4M3413E
800/1A	5	7,5	10	4M3414E

For another ratio, class, burden or double measurement ranges, please consult our Sales Department for more information.

### Technical Specifications

<b>Environmental conditions</b>	
This product is designed to be safe under the following conditions:	
Location:	Indoor use
Operating temperature:	-5°C .. +40°C
Relative humidity:	5% .. 85%, non condensing
Protection degree:	IP20
<b>Application conditions</b>	
Standard:	IEC 61869-2
Rated short-time thermal current:	60 x I <sub>n</sub> / 1s
Continuous thermal current (I <sub>ct</sub> ):	1 x I <sub>n</sub>
Rated insulation level:	0,72/3/-kV
Rated frequency:	50/60Hz
Class of insulation:	E
Primary window dimensions:	Max cable Ø 30 mm Max rail 40x10(13)mm or 30x10(17,5)mm
Secondary terminals:	Screw terminals (max. torque 2Nm) Max. cross-sectional area of cable (stranded) 6mm <sup>2</sup>

### Dimensions



### Wiring Diagram

