

**26003032**

## AC Load break switch SIRCO 3P 315A front operation w/o handle



SIRCO are manually or remotely operated multipolar load break switches. They make and break under load conditions and provide safe isolation. SIRCO are designed for 415 VAC and DC low voltage electrical circuits.

### Strong points

- Reliability and performance
- Safety of property and personnel
- Simplicity
- Easy to install

### General characteristics

- Double positive break indication given through a position indication window, located directly on the product, and by the operating handle.
- Severe load duty categories (AC-22 and AC-23).
- High resistance to damp heat (supplied "tropicalised").

### Compliance with standards

- IEC 60947-3

### Link to the reference

### Classification

UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290

### Commerce

Effective date	1993-04-14
Offer Life Cycle Code	40
Country of origin	TN

### Environmental Sustainability

PEP Filename	SOCO-00069-V01.01-EN.pdf
Climate change - Total - Cradle to Grave [kg CO <sub>2</sub> eq.]	150
Climate change - Total - Cradle to Gate [kg CO <sub>2</sub> eq.]	25

### ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	500
Rated operating voltage [V]	400..500
Rated permanent current Iu [A]	315
Rated permanent current at AC-23, 400 V [A]	315
Rated permanent current at AC-21, 400 V [A]	315
Rated short-time withstand current Icw [kA]	13
Rated operation power at AC-23, 400 V [kW]	160
Switching power at 400 V [kW]	160
Conditioned rated short-circuit current Iq [kA]	100
Number of poles	3

### ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20

### ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No

Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection
<b>Logistics</b>	
GTIN/EAN	3596031118441
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	4.04
Length of the packing unit [m]	0.275
Width of the packing unit [m]	0.155
Depth of the packing unit [m]	0.295
<b>Norms</b>	
Conformity to standards	IEC
<b>SYSTEME</b>	
ReferenceLabel	26003032   SIRCO 3X315A F
<b>Technical Characteristics</b>	
Length of the product unit [mm]	235
Width of the product unit [mm]	230
Depth of the product unit [mm]	110
Weight [kg]	4.04
Control operator	Direct : B2, J1 / External : S2
Number of poles	3
Rated voltage	415 VAC / 500 VDC
Rated current [A]	315
Type	Front Operation
Frame size	B5